

**FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION**

**FORM 600C-01**

**Residential Limited Applications Prescriptive Method C**

**SOUTH 7 8 9**

**Small Additions, Renovations & Building Systems**

Compliance with Method C of Chapter 6 of the Florida Energy Efficiency Code may be demonstrated by the use of Form 600C-01 for additions of 600 square feet or less, site-installed components of manufactured homes, and renovations to single and multifamily residences. Alternative methods are provided for additions by use of Form 600B-01 or 600A-01.

<b>PROJECT NAME: AND ADDRESS:</b>	<b>BUILDER: PERMITTING OFFICE:</b>	<b>CLIMATE ZONE:</b> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9 <input type="checkbox"/>
<b>OWNER:</b>	<b>PERMIT NO.:</b> <input type="text"/>	<b>JURISDICTION NO.:</b> <input type="text"/>

SMALL ADDITIONS TO EXISTING RESIDENCES (600 Square feet or less of conditioned area). Prescriptive requirements in Tables 6C-1, 6C-2 and 6C-3 apply only to the components of the addition, not to the existing building. Space heating, cooling, and water heating equipment efficiency levels must be met only when equipment is installed specifically to serve the addition or is being installed in conjunction with the addition construction. Components separating unconditioned spaces from conditioned spaces must meet the prescribed minimum insulation levels. RENOVATIONS (Residential buildings undergoing renovations costing more than 30% of the assessed value of the building). Prescriptive requirements in Tables 6C-1 and 6C-2 apply only to the components and equipment being renovated or replaced. MANUFACTURED HOMES AND BUILDINGS. Only site-installed components and features are covered by this form. BUILDING SYSTEMS Comply when complete new system is installed.

Please Print

CK

1. Renovation, Addition, New System or Manufactured Home
2. Single family detached or Multifamily attached
3. If Multifamily—No. of units covered by this submission
4. Conditioned floor area (sq. ft.)
5. Predominant eave overhang (ft.)
6. Glass area and type:
  - a. Clear glass
  - b. Tint, film or solar screen
7. Percentage of glass to floor area
8. Floor type and insulation:
  - a. Slab-on-grade (R-value)
  - b. Wood, raised (R-value)
  - c. Wood, common (R-value)
  - d. Concrete, raised (R-value)
  - e. Concrete, common (R-value)
9. Wall type and insulation:
  - a. Exterior:
    1. Masonry (Insulation R-value)
    2. Wood frame (Insulation R-value)
  - b. Adjacent:
    1. Masonry (Insulation R-value)
    2. Wood frame (Insulation R-value)
  - c. Marriage Walls of Multiple Units\* (Yes/No)
10. Ceiling type and insulation:
  - a. Under attic (Insulation R-value)
  - b. Single assembly (Insulation R-value)
11. Cooling system\*  
(Types: central, room unit, package terminal A.C., gas, existing, none)
12. Heating system\*: (Types: heat pump, elec. strip, natural gas, L.P. gas, gas h.p., room or PTAC, existing, none)
13. Air Distribution System\*:
  - a. Backflow damper or single package systems\* (Yes/No)
  - b. Ducts on marriage walls adequately sealed\* (Yes/No)
14. Hot water system:  
(Types: elec., natural gas, other, existing, none)

1.	_____	_____
2.	_____	_____
3.	_____	_____
4.	_____	_____
5.	_____	_____
	Single Pane	Double Pane
6a.	_____ sq. ft.	_____ sq. ft.
6b.	_____ sq. ft.	_____ sq. ft.
7.	_____ %	_____
8a.	R= _____	_____ lin. ft.
8b.	R= _____	_____ sq. ft.
8c.	R= _____	_____ sq. ft.
8d.	R= _____	_____ sq. ft.
8e.	R= _____	_____ sq. ft.
9a-1	R= _____	_____ sq. ft.
9a-2	R= _____	_____ sq. ft.
9b-1	R= _____	_____ sq. ft.
9b-2	R= _____	_____ sq. ft.
9c	_____	_____
10a.	R= _____	_____ sq. ft.
10b.	R= _____	_____ sq. ft.
11.	Type: _____	_____
	SEER/EER: _____	_____
12.	Type: _____	_____
	HSPF/COP/AFUE: _____	_____
13a.	_____	_____
13b.	_____	_____
14.	Type: _____	_____
	EF: _____	_____

\* Pertains to manufactured homes with site installed components.

<p>I hereby certify that the plans and specifications covered by the calculation are in compliance with the Florida Energy Code.</p> <p>PREPARED BY: _____ DATE: _____</p> <p>I hereby certify that this building is in compliance with the Florida Energy Code.</p> <p>OWNER AGENT: _____ DATE: _____</p>	<p>Review of plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed, this building will be inspected for compliance in accordance with Section 553.908, F.S.</p> <p>BUILDING OFFICIAL: _____</p> <p>DATE: _____</p>
--	---

TABLE 6C-1 : PRESCRIPTIVE REQUIREMENTS FOR SMALL ADDITIONS (600 Sq. Ft. and Less), RENOVATIONS TO EXISTING BUILDINGS AND SITE-INSTALLED COMPONENTS OF MANUFACTURED HOMES.

COMPONENT		MINIMUM INSULATION	INSULATION INSTALLED	EQUIPMENT		MINIMUM EFFICIENCY	INSTALLED EFFICIENCY
WALLS	Concrete Block	R-5	_____	COOLING	Central A/C - Split	SEER = 10.0	SEER = _____
	Frame, 2' x 4'	R-11	_____		-Single Pkg.	SEER = 9.7	SEER = _____
	Frame, 2' x 6'	R-19	_____		Room unit or PTAC	EER = 8.5*	EER = _____
	Common, Frame	R-11	_____				
	Common, Masonry	R-3	_____				
CEILINGS	Under Attic	R-30	_____	SPACE HEATING	Electric Resistance	ANY	
	Single Assembly; Enclosed	R-19	_____		Heat pump - Split	HSPF = 6.8	HSPF = _____
	Frame	R-13	_____		- Single Pkg.	HSPF = 6.6	HSPF = _____
	Metal Pans	R-10	_____		Room unit or PTHP	COP = 2.7*	HSPF/ = _____
	Single Assembly; Open	R-11	_____			COP	
	Common, Frame		_____				
FLOORS	Slab-on-grade	No Minimum	_____	HOT WATER	Electric Resistance	EF = .88	EF = _____
	Raised Wood	R-11	_____		Gas; Natural or L.P.	EF = .54	EF = _____
	Raised Concrete	R-5	_____		Fuel Oil	EF = .54	EF = _____
	Common, Frame	R-11	_____				
DUCT	In unconditioned space	R-6	_____				
	In conditioned space	No minimum	_____				

\* See Table 6-3, 6-7

TABLE 6C-2: PRESCRIPTIVE REQUIREMENTS FOR GLASS AREAS IN ADDITIONS ONLY

Maximum percentage glass to floor area allowed is selected by type, overhang length, and solar heat gain coefficient. Maximum% = _____ Installed % = _____								
GLASS TYPE, OVERHANG, AND SOLAR HEAT GAIN COEFFICIENT REQUIRED FOR GLASS PERCENTAGE ALLOWED								
UP TO 20%		UP TO 30%		UP TO 40%		UP TO 50%		
Single	Double	Single	Double	Single	Double	Single	Double	
OH - SHGC	OH - SHGC	OH - SHGC	OH - SHGC	OH - SHGC	OH - SHGC	OH - SHGC	OH - SHGC	
1'-.87	0'-.78	2'-.87	1'-.78	3'-.87	2'-.78	4'-.87	3'-.78	
0'-.75		1'-.75	0'-.61	2'-.75	1'-.61	3'-.75	2'-.61	
		0'-.57		1'-.57	0'-.44	2'-.57	1'-.44	
				0'-.39		1'-.39	0'-.35	
						0'-.30		
Get certified SHGC from the manufacturer or use defaults: Single clear SHGC = .87, double clear SHGC = .78, and single tint SHGC = .75.								

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Exterior Joints & Cracks	606.1	To be caulked, gasketed, weather-stripped or otherwise sealed.	
Exterior Windows & Doors	606.1	Max. 0.3 cfm/sq.ft. window area; .5 cfm/sq.ft. door area.	
Sole & Top Plates	606.1	Sole plates and penetrations through top plates of exterior walls must be sealed.	
Recessed Lighting	606.1	Type IC rated with no penetrations (two alternatives allowed).	
Multi-story Houses	606.1	Air barrier on perimeter of floor cavity between floors.	
Exhaust Fans	606.1	Exhaust fans vented to unconditioned space shall have dampers, except for combustion devices with integral exhaust ductwork.	
Combustion Heating	606.1	Combustion space and water heating systems must be provided with outside combustion air, except for direct vent appliances.	
Water Heaters	612.1	Comply with efficiency requirements in Table 6-12. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required for vertical pipe risers.	
Swimming Pools & Spas	612.1	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have minimum thermal efficiency of 78%.	
Hot Water Pipes	612.1	Insulation is required for hot water circulating systems (including heat recovery units).	
Shower Heads	612.1	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
HVAC Duct Construction, Insulation & Installation	610.1	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated and installed in accordance with the criteria of Section 610.1. Ducts in attics must be insulated to a minimum of R-6.	
HVAC Controls	607.1	Separate readily accessible manual or automatic thermostat for each system.	

GENERAL DIRECTIONS:

- On Table 6C-1 indicate the R-value of the insulation being added to each component and the efficiency levels of the equipment being installed. All R-values and efficiencies installed must meet or exceed the minimum values listed. Components and equipment neither being added nor renovated may be left blank.
- ADDITIONS ONLY. Determine the percentage of new glass to conditioned floor area in the addition as follows. Total the areas of all glass windows, sliding glass doors and glass door panels. Double the area of all non-vertical roof glass and add it to the previous total. When glass in existing exterior walls is being removed or enclosed by the addition, an amount equal to the total area of this glass may be subtracted from the total glass area. Divide the adjusted glass area total by the conditioned floor area of the addition. Multiply by 100 to get the percent. Find the largest glass percentage under which your calculated percentage falls on Table 6C-2. Prescriptives are given by the type of glass (Single or Double pane) and the overhang (OH) paired with a solar heat gain coefficient (SHGC). For a given glass type and overhang, the minimum solar heat gain coefficient allowed is specified. Actual glass windows and doors previously in the exterior walls of the house and being reinstalled in the addition do not have to comply with the overhang and solar heat gain coefficient requirements on Table 6C-2. All new glass in the addition must meet the requirement for one of the options in the glass percentage category you indicated. The overhang (OH) distance is measured perpendicularly from the face of the glass to a point directly under the outermost edge of the overhang.
- RENOVATIONS ONLY. Replacement glass needs to meet the following requirements. Any glass type and solar heat gain coefficient may be used for glass areas which are under at least a two foot overhang and whose lowest edge does not extend further than 8 feet from the overhang. Glass areas being renovated that do not meet this criteria must be either single-pane tinted, double-pane clear or double-pane tinted.
- BUILDING SYSTEMS. Comply when new system is installed for system installed.
- Complete the information requested on the top half of page 1.
- Read "Minimum Requirements for Small Additions and Renovations", Table 6C-3, and check all applicable items.
- Read, sign and date the "Owner/Agent" certification statement on page 1.